



469.00 EUR

incl. 19% VAT, plus [shipping](#)

- Quad-Channel !
- Extended Temperature !
- -40 to 85°C !

Support: [Specifications](#)

The DarkCrystal SD Capture Mini-PCIe Quad simultaneously preserves up to four channels from multiple composite input sources, reducing system costs. DarkCrystal SD Capture Mini-PCIe Quad makes use of exclusive hardware design guarantying fast response and solid performance for high-density SD capture or encoding demands.

The DarkCrystal SD Capture Mini-PCIe Quad simultaneously preserves up to 4 channels from multiple composite input sources, reducing system costs.

- Supports extended operating temperatures from -40 to 85°C
- Video capture with composite input
- 4-channel concurrent capture solution
- Standard minicard dimension
- Mainstream programming languages supported
- DirectShow compatible

Module Type

PCI Express Minicard

Input

4-ch Composite

Audio(L/R)

Video Resolution

NTSC (29.97Hz): 720 x 480, 640 x 480, 360 x 240, 320 x 240, 180 x 120, 160 x 120

Color Adjustment

PAL (25Hz): 720 x 576, 640 x 480, 360 x 288, 180 x 144
Brightness, Contrast, Hue (NTSC only), Saturation

Operating Environment

Temperature: -40 to +85 ■
Humidity: 0 to 90% RHNC

Storage Environment**Temperature: -50 to +85 ■****Humidity: 0 to 90% RHNC****Power Requirement****1.13W****Dimensions (L x W)****50.95 x 30mm****System Requirements****CPU****Intel® Pentium®4 3.0 GHz****AMD Athlon™ 64 3200+****Memory****512 MB RAM****VGA****VGA card with support for DirectX9.0c or above****Sound Card****Yes****Supported OS****Windows 7/8.1/10 (32/64 bits), Linux (32/64 bits)***